

1.4 Technical data, lube oil system

Oil filling, integrated lube oil

tank in the LGD gear unit	:	nominal	1600 l
		maximum	2200 l
Drawing	:	lube oil system	Drg. No. 50021160

1.4.1 Tank heating

Heating element	:	HBE	Type R 2" x 2000 mm
Voltage	:		3 x 480 V
Frequency	:		
Power	:		

1.4.2 Lube oil pump unit

Electric motor
Power
Speed
Voltage
Frequency
Screw pump
Capacity
Working pressure
Total weight



Genuine Parts & Service

Alle Angaben für eine Nachbestellung dieses Artikels enthält der in diesem Etikett integrierte Memo-Sticker zum Einkleben in die Bedienungsanleitung Ihres BOLLFILTERs.

The memo sticker embedded in this label comprises all information needed for a repeat order of this item. Stick it into the operations manual of your BOLLFILTER.

↓ **Hier abziehen! Lift off here!** ↓



Genuine Parts & Service

BOLL & KIRCH Filterbau GmbH
Postfach 1420, D-50143 Kerpen
Tel.: ++49 (0)2273/562-0
Fax: ++49 (0)2273/562-223
Internet: <http://www.bollfilter.de>

Auftrag: 3849557 Pos: 1
Art.Nr.: 1938648
Bez. : Sternsieb
300/250

1.4.3 Lube oil filter

Duplex filter (PN 16 / DN 65)	:	BOLL & KIRCH	Type 2.04.5.170.500 DN80 PN16
Filter insert	:	Filter mesh	25 µm
Flow rate	:		approx. 209 l/min
Working pressure	:	4 - 9 bar (58.02 – 130.54 psi)	
Weight	:		approx. 107 kg