

**Schalldruckpegel [dB(A)], Baureihe IL**  
**noise level [dB(A)], type IL**  
**niveau de pression acoustique [dB(A)], version IL**  
**Nivel sonoro [dB(A)], variante de serie IL**  
**Livello di pressione acustica [dB(A)], serie IL**

Bg Frame size HA Tamaño mod.	400V 50Hz	460V 60Hz	400V 50Hz	460V 60Hz	400V 50Hz	460V 60Hz
	3 ~ Y 2-polig	3 ~ Y 2-polig	3 ~ Y 4-polig	3 ~ Y 4-polig	3 ~ Δ 4-polig	3 ~ Δ 4-polig
63	47	55	/	/	/	/
71	51	57	/	/	/	/
80	55	59	/	/	/	/
90	58	66	/	/	/	/
100	59	70	44	51	/	/
112	61	70	44	49	/	/
132	69	75	54	59	/	/
160	74	77	57	63	/	/
180	75	80	59	64	/	/
200	75	81	60	66	/	/
204	/	/	65	70	66	72
225	/	/	64	70	66	71
249	/	/	65	69	66	72
250	/	/	70	71	70	76
280	/	/	69	72	71	77
315	/	/	70	73	72	77

mit b-seitigem Referenzlagerschild  
 with bearing shield of reference on side b  
 avec de référence flasque latérale b  
 placa de referencia en el lado b  
 con targhetta cuscinetti di riferimento lato b