

# HOW TO ORDER

SE3        (     )

**HOUSING TYPE** \_\_\_\_\_

- 7: Ex proof type
- 8: General type

**HOUSING COVER** \_\_\_\_\_

- 0: Aluminum cover
- 1: Aluminum cover with LED lamp
- 2: Plastic cover
- ※ 1 and 2 are not available for SE37.

**MODEL** \_\_\_\_\_

- 0: Standard
- 2: Shaft protective tube
- 4: High temperature
- 5: High temperature shaft protective tube

**SUPPLY VOLTAGE** \_\_\_\_\_


- A: 110Vac, 50/60Hz
- B: 220Vac, 50/60Hz
- C: 240Vac, 50/60Hz
- D: 24Vac, 50/60Hz
- E: 24Vdc

**CONNECTION** \_\_\_\_\_


Size for flange or screw		Specification	
C: 3/4"	I: 4"	M: 5kg/cm <sup>2</sup>	Z : PN40
D: 1"	J: 5"	N: 10kg/cm <sup>2</sup>	Q: PT
3: 1-1/4"	K: 6"	O: 150Lbs	R: PF(G)
E: 1-1/2"	S: Special	P: 300Lbs	T: BSP
F: 2"		W: PN10	U: NPT
G: 2-1/2"		X : PN16	S : Special
H: 3"		Y : PN25	

**PADDLE SHAPE** (mm) \_\_\_\_\_


- G: Cross paddle
- H: Scimitar paddle
- I : 100x30 (WxH)
- K: Folding paddle
- S: Special
- : None




Material: PC



Material: PC



Material: Stainless steel



Material: Stainless steel

**CABLE LENGTH** (mm) \_\_\_\_\_

- 0500 : below 500mm
  - 1000 : 501~1000mm
  - 1500 : 1001~1500mm
- ※ 500mm per unit  
 ※ Standard length 300mm

⋮