


# POLYURETHANE TIMING BELTS

## IMPERIAL-SERIES

**H=T1/2"**  
(12.7mm)



**STEEL** Tension Member — standard  
**KEVLAR®** Tension Member — optional




### OPEN ENDED – M



Pulleys  
page 168

#### Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR
- T-Cover
- DL
- DR



**Widths:** Standard Belt Widths (in between widths available):

in inch:	0.5	0.75	1.0	1.5	2.0	3.0	4.0	6.0
in mm:	12.7	19.05	25.4	38.1	50.8	76.2	101.6	152.4

**Lengths:** Any length available – Stock Rolls: 50 meters (164 feet)

#### Ordering example:

**BRECO Timing Belt** 50.8 T1/2" / 2032 M or 800 H 200 M

Belt Width	_____	_____	_____	_____	_____	_____	_____	_____
Pitch	_____	_____	_____	_____	_____	_____	_____	_____
Length	_____	_____	_____	_____	_____	_____	_____	_____
Open Ended Length Code M	_____	_____	_____	_____	_____	_____	_____	_____




### SPLICED AND WELDED ENDLESS – V



Pulleys  
page 168

#### Available Options (page 149):

- PAZ
- PAR
- PAZ-PAR
- T-Cover
- DL
- DR



**Widths:** Standard Belt Widths (in between widths available):

in inch:	0.5	0.75	1.0	1.5	2.0	3.0	4.0	6.0
in mm:	12.7	19.05	25.4	38.1	50.8	76.2	101.6	152.4

**Lengths:** Minimum Joined Length: 876.3 mm (34.5 inches)  
Length of timing belt can be specified in one tooth increments

#### Ordering example:


**BRECO Timing Belt** 50.8 T1/2" / 2032 V or 800 H 200 V

Belt Width	_____	_____	_____	_____	_____	_____	_____	_____
Pitch	_____	_____	_____	_____	_____	_____	_____	_____
Length	_____	_____	_____	_____	_____	_____	_____	_____
Joined Length Code V	_____	_____	_____	_____	_____	_____	_____	_____

# POLYURETHANE TIMING BELTS

## IMPERIAL-SERIES

**H=T 1/2"**  
(12.7mm)



**STEEL Tension Member — standard**



### TRULY ENDLESS - BFX



Pulleys  
page 168

**Widths:** Standard Belt Widths (in between widths available):

in inch:	0.5	0.75	1.0	1.5	2.0	3.0	4.0
in mm:	12.7	19.05	25.4	38.1	50.8	76.2	101.6


Length/Pitch Code	Length in mm	Number of Teeth
285 H	723.9	57
300 H	762.0	60
315 H	800.1	63
330 H	838.2	66
345 H	876.3	69
360 H	914.4	72
375 H	952.5	75
390 H	990.6	78
405 H	1028.7	81
420 H	1066.8	84
450 H	1143.0	90
480 H	1219.2	96
510 H	1295.4	102
540 H	1371.6	108
570 H	1447.8	114
600 H	1524.0	120

Length/Pitch Code	Length in mm	Number of Teeth
630 H	1600.2	126
660 H	1676.4	132
700 H	1778.0	140
750 H	1905.0	150
800 H	2032.0	160
850 H	2159.0	170
900 H	2286.0	180
1000 H	2540.0	200
1100 H	2794.0	220
1250 H	3175.0	250
1400 H	3556.0	280
1700 H	4318.0	340
2000 H	5080.0	400
2300 H	5842.0	460
2600 H	6604.0	520
3000 H	7620.0	600

Further lengths up to 16,002.00 mm (630 inches) available.  
Length of timing belt can be increased in increments of one tooth from minimum length of 723.9 mm (28.5 inches).

**Available Options (page 149):**

- PAZ
- T-Cover
- DL
- DR



**Ordering example:**

**BRECOFLEX Timing Belt 50.8 T1/2" / 1905 BFX or 750 H 200 BFX**

Belt Width	_____	_____	_____	_____	_____	_____
Pitch	_____	_____	_____	_____	_____	_____
Length	_____	_____	_____	_____	_____	_____
Truly Endless Length Code BFX	_____	_____	_____	_____	_____	_____